

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

B15
1. (currently amended): A glove holding member for supporting protective gloves in a system for transporting and/or cleaning of slaughter equipment, said member (14) being formed substantially in the shape of a human hand with five fingers (15) and being adapted to distend a protective glove positioned on it in a common plane containing the fingers, the fingers being formed by a configuration of bar members mounted in a common base and being adapted to distend a protective glove positioned in a common plane containing the fingers, each bar member being formed from a single piece of wire material having ends secured in two mounting holes provided in said base and being bent into a hair-needle shape characterized in that the fingers (15, 37) are formed by a configuration of bar members (151) mounted in a common base (16, 41), said bar members (151) extending substantially in symmetry with respect to said common plane and being formed to distend the a corresponding finger member of a protective glove in a direction transverse to said common plane.

2. (canceled).

23 (currently amended): A glove holding member as claimed in claim 21, ~~characterized in that wherein said configuration of bar members comprises distinct sets (171, 172) of mounting~~

B/S
cont

holes (17) for distinct pairs (152, 153) of ~~extreme~~outer bar members, (151) each of the outer bar members having ends secured in a distinct set of mounting holes, which are ~~are each~~ positioned in the base (16) along a common line transverse to said common plane, the ~~individual bar members (151) of each of pair (152, 153)~~ outer bar members projecting from the respective set (171, 172) of mounting holes (17) with an angular displacement.

3/4 (currently amended): A glove holding member as claimed in claim ²~~3~~, ~~characterized in that~~wherein a distal end part (154) of an outermost bar member ~~a most extreme bar member~~ (151) of each of said distinct pairs (152, 153) is bent outward from the finger configuration of bar members (151) in said common plane.

4/5 (currently amended). A glove holding member as claimed in claim 1, ~~characterized in that~~wherein the configuration of bar members (151) is surrounded by a ring member (152) arranged to be displaceable in the longitudinal direction of the bar members (151) to bring the bar members together by displacement in a direction towards the distal ends of the bar members and to allow the bar members to spread out from each other by displacement in a direction towards the base.

5/6 (currently amended): A combination of a glove ~~Use of a~~ holding member as claimed in ~~claim 1 in a system for~~ for supporting protective gloves in a slaughterhouse and a system for transporting and/or cleaning of slaughterhouse equipment, said system comprising at least one

BK
conf

transporting and/or cleaning device for slaughter equipment, said system being provided with a stationary glove holder mounting means for holding characterized in that the base (16, 41) of said glove holder member (14, 37) formed substantially in the shape of a human hand with five fingers and formed by a configuration of bar members mounted in a common base provided with an engagement means for releasable engagement with said glove holder mounting means, said glove holder mounting means comprising a projecting hook member and a projecting guide member and said engagement means comprising an extension of said base of the glove holding member provided with an opening for engagement with said hook member and a recess engageable by said guide member~~is provided with engagement means for releasable engagement with glove holder mounting means provided by transporting and/or cleaning device.~~

7. (canceled). ✓

6/8 (currently amended): The combination Use as claimed in claim ⁵6, characterized in ~~that~~ wherein said glove member mounting means comprise a support member ~~18, 19~~ and a releasable pawl member, ~~(20, 21)~~ and ~~that~~ the base (16) of the glove holding member (14) comprises a substantially rectangular frame structure with end walls ~~(161)~~ and side walls (162) of shallow height, opposed longitudinal edges ~~(162, 164)~~ of said side walls (162) are each being formed with a recess, wherein the recesses are means ~~(165, 166)~~ engageable by a support member ~~(19)~~ and a releasable pawl member ~~(21)~~, respectively.

B

29. (currently amended): The combination Use as claimed in claim ~~6~~⁵, characterized in that wherein said glove holder ~~said~~ mounting means comprises tubular support members (40) and that the base (41) of the glove holding member (37) comprises a bent bar (38) having a first part (39) engageable with said tubular support members (40) and a second part (43) for locking the glove holding member with respect to the tubular support members (40).

30. (currently amended): The combination Use as claimed in claim ~~6~~⁵, characterized in that wherein said transporting and/or cleaning device comprises a trolley for transportation of slaughter equipment to and from a cleaning installation.

11.-16. (withdrawn).